

## 10.8V LI-ION 3 X 360° CROSS LINE LASER (GREEN BEAM)

10.8V XR

### DCE089D1G

Beam Colour	Green
Accuracy	+/-3 mm @ 10m
Self-Levelling Range	+/-4°
Max. Working Range with Detector	30-50m
IP Rating	65
Number of Beams	3 - Horizontal, Vertical, Side
Tripod Connection	1/4" x 5/8"
Pendulum Lock	Yes
Laser Class	2
Modes	1 x 360° Horizontal, 1 x 360° Vertical, 2nd 360° Vertical



ALSO AVAILABLE AS:

### DCE089NG



## 10.8V LI-ION 2 SPOT CROSS LINE LASER (RED BEAM)

10.8V XR

### DCE0822D1R

Beam Colour	Red
Accuracy	+/-3 mm @ 10m Spot +/-2 @ 10m
Self-Levelling Range	+/-4°
Max. Working Range Line/Spot	20m/50m
IP Rating	65
Number of Beams	7 - Cross Line plus 5 spots
Tripod Connection	1/4" x 5/8"
Pendulum Lock	Yes
Laser Class	2
Modes	Vertical Only, Horizontal Only, Cross Line, 3 Spot Only: Up, Down, Front, 5 Spot Only: Up, Down, Front, Both Sides



## 10.8V LI-ION 2 SPOT CROSS LINE LASER (GREEN BEAM)

10.8V XR

### DCE0822D1G

Beam Colour	Green
Accuracy	+/-3 mm @ 10m Spot +/-2 @ 10m
Self-Levelling Range	+/-4°
Max. Working Range Line/Spot	30m/50m
IP Rating	65
Number of Beams	7 - Cross Line plus 5 spots
Tripod Connection	1/4" x 5/8"
Pendulum Lock	Yes
Laser Class	2
Modes	Vertical Only, Horizontal Only, Cross Line, 3 Spot Only: Up, Down, Front, 5 Spot Only: Up, Down, Front, Both Sides

