

EXTREME[®] DEWALT[®] BONDED ABRASIVES OSA[®]

Disc diameter
Date of expiry
Application
Max. speed (rpm)*
OSA no.
Safety symbols
Disc thickness
Bore diameter
Cat. No.
Disc material
European standard
OSA-Logo
EAN

MAX RPM
5,600min⁻¹rpm
MAX 60m/s

A24R7BF
EN12413

OSA

DX7987-AE



Ø230x3.0x22.2mm

Type 1 Flat Discs
Type 42 Depressed Discs

METAL CUTTING DISCS



Ø100-230 mm



APPLICATIONS

- Cutting ferrous metals such as steel, iron, rebar and welds

FEATURES

- Professional grade aluminium oxide
- Premium resin bond
- Reinforced fibre glass

FOR USE WITH

Angle grinders.





DEPRESSED CENTRE

| Cat. No. | Diameter mm | Bore mm | Thickness mm | Grit/Bond | Pack Qty. |
|-----------|-------------|---------|--------------|-----------|-----------|
| DX7907-AE | 100 | 16.0 | 3.0 | A24R7BF | 25 |
| DX7927-AE | 115 | 22.2 | 3.0 | A24R7BF | 25 |
| DX7947-AE | 125 | 22.2 | 3.0 | A24R7BF | 25 |
| DX7967-AE | 180 | 22.2 | 3.0 | A24R7BF | 25 |
| DX7987-AE | 230 | 22.2 | 3.0 | A24R7BF | 25 |

METAL GRINDING DISCS



Ø100-230 mm



APPLICATIONS

- For general metal grinding applications on ferrous and non-ferrous metals, including weld and surface preparation

FEATURES

- Professional grade aluminium oxide
- Reinforced fibre glass

FOR USE WITH

Angle grinders.





DEPRESSED CENTRE

| Cat. No. | Diameter mm | Bore mm | Thickness mm | Grit/Bond | Pack Qty. |
|-----------|-------------|---------|--------------|-----------|-----------|
| DX7901-AE | 100 | 16.0 | 6.0 | A30R7BF | 10 |
| DX7921-AE | 115 | 22.2 | 6.0 | A30R7BF | 10 |
| DX7941-AE | 125 | 22.2 | 6.0 | A30R7BF | 10 |
| DX7961-AE | 180 | 22.2 | 6.0 | A30R7BF | 10 |
| DX7981-AE | 230 | 22.2 | 6.0 | A30R7BF | 10 |

STAINLESS STEEL CUTTING AND THIN CUTTING DISCS



Ø100-230 mm



APPLICATIONS

- Fast cutting and long life in harder metals

FEATURES

- Professional grade aluminium oxide
- Reinforced fibre glass
- Premium resin bond


FOR USE WITH

Angle grinders and cut-off saws.



FLAT

| Cat. No. | Diameter mm | Bore mm | Thickness mm | Grit/Bond | Pack Qty. |
|-----------|-------------|---------|--------------|------------|-----------|
| DT3440-QZ | 100 | 16.0 | 1.0 | A60 TBF | 25 |
| DT3442-QZ | 115 | 22.2 | 1.0 | A60 TBF | 25 |
| DT3445-QZ | 125 | 22.2 | 1.0 | A60 TBF | 25 |
| DX8055 | 230 | 22.2 | 1.9 | AS46INOXBF | 25 |





DEPRESSED CENTRE

| Cat. No. | Diameter mm | Bore mm | Thickness mm | Grit/Bond | Pack Qty. |
|------------|-------------|---------|--------------|---------------|-----------|
| DX7907S-AE | 100 | 16.0 | 3.0 | AS24R7BF Inox | 25 |
| DX7927S-AE | 115 | 22.2 | 3.0 | AS24R7BF Inox | 25 |
| DX7947S-AE | 125 | 22.2 | 3.0 | AS24R7BF Inox | 25 |
| DX7967S-AE | 180 | 22.2 | 3.0 | AS24R7BF Inox | 25 |
| DX7987S-AE | 230 | 22.2 | 3.0 | AS24R7BF Inox | 25 |

STAINLESS STEEL GRINDING DISCS



Ø100-230 mm



APPLICATIONS

- Fast cutting and long life in harder metals

FEATURES

- Professional grade aluminium oxide and silicone carbide

FOR USE WITH

Angle grinders.



DEPRESSED CENTRE

| Cat. No. | Diameter mm | Bore mm | Thickness mm | Grit/Bond | Pack Qty. |
|------------|-------------|---------|--------------|---------------|-----------|
| DX7901S-AE | 100 | 16.0 | 6.0 | AS30R7BF Inox | 10 |
| DX7921S-AE | 115 | 22.2 | 6.0 | AS30R7BF Inox | 10 |
| DX7961S-AE | 180 | 22.2 | 6.0 | AS30R7BF Inox | 10 |
| DX7981S-AE | 230 | 22.2 | 6.0 | AS30R7BF Inox | 10 |