

Hand Stackers

FEATURES



- Used for loading goods onto or unloading goods from pallets & stacking goods
- Compact truck body, especially suitable for narrow aisles and small spaces
- Seal rings conforming to German standards ensure excellent performance
- Frame constructed of high-strength C type steel
- The cylinders use high precision drawn tubes which prevents the seal rings from damage and leakage
- Press resistant caster bracket protects the operator from injuries
- Foot pedal provides an additional option for convenient lifting

| | |
|-----------------|------------|
| MODEL | H15 |
| LOAD CAPACITY | 1500 kgs |
| LOAD CENTER | 600 mm |
| MAX LIFT HEIGHT | 1600 mm |
| MIN FORK HEIGHT | 85 mm |
| MIN MAST HEIGHT | 2030 mm |
| FORK LENGTH | 1150mm |
| FORK WIDTH | 330-740 mm |
| OVERALL LENGTH | 1670 mm |
| OVERALL WIDTH | 834 mm |
| WEIGHT | 345 kgs |



Model H15

Semi-electric Hand Stackers

FEATURES



- Used for loading goods onto or unloading goods from pallets and stacking goods
- Compact truck body, especially suitable for narrow aisles and small spaces
- Efficient and energy-saving power unit
- Overload protection
- Frame constructed of high-strength C type steel
- Throttle valve with pressure compensation function enables stable & reliable lowering
- Hydraulic reservoir with filter, effectively prevents contamination by foreign matters
- Ergonomic handle to ensure optimum safety and comfort
- Mechanically assisted steering system for easy travel
- Anti-pressure caster frame

| | |
|-----------------|------------|
| MODEL | S15 |
| LOAD CAPACITY | 1500 kgs |
| LOAD CENTER | 600 mm |
| MAX LIFT HEIGHT | 3000 mm |
| MIN FORK HEIGHT | 85 mm |
| MIN MAST HEIGHT | 2060 mm |
| FORK LENGTH | 1150mm |
| FORK WIDTH | 330-830 mm |
| OVERALL LENGTH | 1800 mm |
| OVERALL WIDTH | 745 mm |
| OVERALL HEIGHT | 2025 mm |
| WEIGHT | 467 kgs |
| BATTERY | 12V |



Model S15