




## PGG 3/1

Petrol-operated, 2.8 kW power rating, puncture-proof wheels and 15 litre tank: synchronous generator PGG 3/1 for up to 12 hours of work independent of external power sources at many job sites.



### 1 Extraordinary ease of use

- High mobility thanks to the foldable push handle and puncture-proof wheels.
- Electro start function for the convenient and quick start of the petrol engine.

### 2 Ultimate reliability and safety

- With overload and oil shortage protection as well as tubular steel frame for maximum safety.
- With automatic voltage regulator (AVR) for the operation of sensitive electronic devices.

### 3 Very powerful

- 230 V synchronous generator reliably provides continuous power of 2.8 kW.
- Powerful petrol engine for applications of min. 6.5 hours per tank filling.

### 4 Operation of Kärcher high-pressure cleaners

- For use of high-pressure cleaners in areas without an external power supply.
- Suitable for selected, single-phase high-pressure cleaners.



## PGG 3/1

- Convenient electric start function with key switch
- Foldable push handle and puncture-proof tyres
- Robust cage frame

### Technical data

<b>Order no.</b>	1.042-207.0	
<b>EAN code</b>	4054278547923	
<b>Voltage</b>	<b>V</b>	230
<b>Phase</b>	<b>Ph</b>	1
<b>Rated performance</b>	<b>kW</b>	2.8
<b>Max. performance</b>	<b>kW</b>	3
<b>Motor type</b>	Petrol	
<b>Cubic capacity</b>	<b>cm<sup>3</sup></b>	208
<b>Motor rating</b>	<b>kW / hp</b>	5.1 / 6.9
<b>Tank capacity</b>	<b>l</b>	15
<b>Runtime at 50% output</b>	<b>h</b>	12
<b>Runtime at 100% output</b>	<b>h</b>	6.5
<b>Weight</b>	<b>kg</b>	51.7 / 52 / 56.1
<b>Dimensions (L × W × H)</b>	<b>mm</b>	645 × 622 × 549

### Equipment

Operating state display	■
DC output (12 V)	■
Protection class IP 23	■
Low oil and overload protection	■
Fuel gauge	■
Single phase socket type F (Schuko)	■
Automatic Voltage Regulation (AVR)	■

■ Included in the scope of supply.